

Voltage amplitude multiplying circuitsPatent Number: ☐ US4000412

Publication

date: 1976-12-28

Inventor(s): ROSENTHAL BRUCE DAVID; DINGWALL ANDREW GORDON FRANCIS

Applicant(s): RCA CORP

Requested

Patent: ☐ DE2525057

Application

Number: US19750578913 19750519

Priority Number

(s): GB19740024898 19740605

IPC

Classification: H03K3/64; H03K3/353; H03K17/60

EC

Classification: G04G1/00E, H02M3/07

Equivalents:

AU8170675, AU8171475, CA1035415, CA1035416, ☐ CH600663, ☐ CH600664, ☐ DE2525075,
☐ FR2274165, ☐ FR2274166, ☐ GB1504867, HK11383, ☐ IT1038313, ☐ IT1038314,
JP1022871C, JP1130300C, ☐ JP51007444, ☐ JP51010325, JP55003898B, JP57018423B

Abstract

Circuits for generating pulsating potentials and voltage levels outside the range of, and/or of greater magnitude than, the operating potential applied to the circuits. Each circuit includes first and second transistors for applying a first voltage to one plate of a capacitor and a second voltage to the other plate of the capacitor, during one time interval. During a subsequent time interval, the first and second transistors are turned off and a third transistor applies the second potential to the one plate of the capacitor. The change in the potential at the one plate of the capacitor is coupled to the other plate of the capacitor at which is produced an output potential outside the range of the first and second voltages. The potential difference between the first voltage and the output potential is greater in amplitude than the potential difference between the first and second voltages. The circuit may also include means alternately applying the first voltage and then the output potential to an output point for generating pulsating signals of greater amplitude than the magnitude of the applied potential. The outputs of two or more circuits may be combined to produce direct current (d.c.) levels. Also included are circuits which operate from a pulsating source of operating potential.

Data supplied from the esp@cenet database - I2

- [54] **VOLTAGE AMPLITUDE MULTIPLYING CIRCUITS**
- [75] Inventors: **Bruce David Rosenthal**, Highland Park; **Andrew Gordon Francis Dingwall**, Somerville, both of N.J.
- [73] Assignee: **RCA Corporation**, New York, N.Y.
- [22] Filed: **May 19, 1975**
- [21] Appl. No.: **578,913**
- [30] **Foreign Application Priority Data**
- June 5, 1974 United Kingdom 24898/74
- [52] U.S. Cl. **307/208; 307/110; 307/246; 307/264; 307/296 A; 307/DIG. 1**
- [51] Int. Cl.² **H03K 3/64; H03K 3/353; H03K 17/60**
- [58] **Field of Search** **307/108, 109, 110, 246, 307/264, 269, 296 R, 296 A, 279, 208, DIG. 1, 240, 251; 320/1**

- [56] **References Cited**
- UNITED STATES PATENTS**
- | | | | |
|-----------|--------|-------------------|-----------|
| 3,509,375 | 4/1970 | Gormley | 307/246 X |
| 3,790,812 | 2/1974 | Fry | 307/246 X |
| 3,900,746 | 8/1975 | Kraft et al. | 307/264 |

Primary Examiner—John S. Heyman
 Assistant Examiner—Larry N. Anagnos
 Attorney, Agent, or Firm—H. Christoffersen; Henry I. Schanzer

[57] ABSTRACT

Circuits for generating pulsating potentials and voltage levels outside the range of, and/or of greater magnitude than, the operating potential applied to the circuits. Each circuit includes first and second transistors for applying a first voltage to one plate of a capacitor and a second voltage to the other plate of the capacitor, during one time interval. During a subsequent time interval, the first and second transistors are turned off and a third transistor applies the second potential to the one plate of the capacitor. The change in the potential at the one plate of the capacitor is coupled to the other plate of the capacitor at which is produced an output potential outside the range of the first and second voltages. The potential difference between the first voltage and the output potential is greater in amplitude than the potential difference between the first and second voltages. The circuit may also include means alternately applying the first voltage and then the output potential to an output point for generating pulsating signals of greater amplitude than the magnitude of the applied potential. The outputs of two or more circuits may be combined to produce direct current (d.c.) levels. Also included are circuits which operate from a pulsating source of operating potential.

22 Claims, 9 Drawing Figures

